


ADDENDUM TO 400030-024 and 400030-106, INSTALLATION AND OPERATION MANUALS For SS2000D3-230 and SS2000D3i-230 UNITS THE FOLLOWING COMMENTS APPLY.

3.5.5 - AC POWER CONNECTIONS TO THE UNIT

Connect the two (2) AC IN terminals to the input AC line. The line voltage can vary between 187 VAC and 264 VAC 50/60 Hertz. Do not exceed the voltage rating of the drive and motor. Damage may occur if the ratings are not observed.



RECOMMENDED MOTORS

Motors used with the SS2000D3-230 and SS2000D3i-230 units need a higher insulation rating than standard motors. The following is a listing of the motors which we recommend for use with the SS2000D3-230/D3i-230. This supercedes the list in Section 4.4 - Motor Compatibility.

KM Series CE Compliant Motors	
KMLC061F03	KMTC061F03
KMLC062F03	KMTC062F03
KMLC063F04	KMTC063F04
KMLC091F05	KMTC091F05
KMLC092F07	KMTC092F07
KMLC093F07	KMTC093F07

NOTES

- 1) The SS2000D3-230 and SS2000D3i-230 units are **Not** U.L. recognized.
- 2) The SS2000D3-230 and SS2000D3i-230 units are **Not** CE compliant.
- 3) Duty Cycle limits may be required to keep the motor temperature within its rating.

Web Site: www.superiorelectric.com



383 MIDDLE STREET • BRISTOL, CT 06010
Tel: (860) 585-4500 • FAX: (860) 589-2136

